

Appostar

YOUR RELIABLE GLOBAL PARTNER

Customer Pole Display

CPD-5000 CPD-3220



Features

CPD-5000

- Backlight adjustment up to 17 colors
- 5 color options on front panel
- USB power source for cable reduction and cost saving
- Low power consumption for energy saving
- Innovative hinge design for quick angle adjustment
- Built-in full-speed USB and high speed RS232 up to 115,200 bps

CPD-3220

- 20 char. x 2 line Vacuum Fluorescent Display
- Eye-catching bright blue-green font
- Innovative hinge design for quick angle adjustment
- Built-in full-speed USB and high speed RS232 up to 115,200 bps

APPOSTAR Technology Co.,Ltd.

7F, No. 207, Sec. 3 Beishin Rd.,
Shindian City, Taipei 231 Taiwan
Tel: 886-2-8913-1618
Fax: 886-2-8913-1699
Email: sales@appostar.com
<http://www.appostar.com>

© 2011 APPOSTAR Technology Co., Ltd. All rights reserved.

Customer Pole Display

CPD-5000 CPD-3220 Specification

Model	CPD-5000	CPD-3220																		
Display Method	Mono. Liquid Crystal Display	Vacuum fluorescent Display																		
Number of Characters	30 columns x 4 lines/2 lines in double height (alphanumeric) 15 columns x 4 lines/2 lines in double height (Chinese character)	40 characters (20 columns x 2 lines)																		
Display Color	<table border="1"> <tr> <td>1. Cyan</td> <td>10. Orange</td> </tr> <tr> <td>2. Light Blue</td> <td>11. Violet</td> </tr> <tr> <td>3. Purple</td> <td>12. Light Pink</td> </tr> <tr> <td>4. Blue</td> <td>13. Pink</td> </tr> <tr> <td>5. Lake Green</td> <td>14. Dark Pink</td> </tr> <tr> <td>6. Apple Green</td> <td>15. Magenta</td> </tr> <tr> <td>7. Green</td> <td>16. Red</td> </tr> <tr> <td>8. Yellow</td> <td>17. Pale</td> </tr> <tr> <td>9. Light Orange</td> <td></td> </tr> </table>	1. Cyan	10. Orange	2. Light Blue	11. Violet	3. Purple	12. Light Pink	4. Blue	13. Pink	5. Lake Green	14. Dark Pink	6. Apple Green	15. Magenta	7. Green	16. Red	8. Yellow	17. Pale	9. Light Orange		Blue-green
1. Cyan	10. Orange																			
2. Light Blue	11. Violet																			
3. Purple	12. Light Pink																			
4. Blue	13. Pink																			
5. Lake Green	14. Dark Pink																			
6. Apple Green	15. Magenta																			
7. Green	16. Red																			
8. Yellow	17. Pale																			
9. Light Orange																				
Brightness	100 cd/m ²	700 cd/m ²																		
Character Type	I. 96 alphanumeric II. 13 sets of international character III. One set user downloadable character IV. One of the following languages is optional: <ul style="list-style-type: none"> ■ Traditional Chinese (BIG-5) ■ Simplified Chinese (GB2312) ■ Japanese (Shift-JIS) ■ Korean (KSC5610) ■ Thai 	I. 96 alphanumeric characters II. 14 sets of international characters: USA, France, Germany, UK, Sweden, Denmark I and II, Italy, Spain, Norway, Japan (Katakana), Slavonic, Russian and Portuguese III. One set of user downloadable characters																		
Font Size	8x16 / 8x32 alphanumeric 16x16 / 16x32 multi byte characters	5x7 (dot matrix) alphanumeric 9.03 mm x 5.25 mm																		
Command Set	1. BA63G 2. ESC/POS 3. WD-304	1. EPSON ESC/POS 2. ADM787/788 3. EMAX (AEDEX) 4. UTC/S, UTC/P 5. CD5220 6. DSP-800 (option)																		
Interface	<ul style="list-style-type: none"> ■ RS-232: 4800/9600/19200/38400/115200 bps ■ USB 2.0 	<ul style="list-style-type: none"> ■ RS-232: 9600/19200/38400/115200 bps ■ USB 2.0 																		
Option	<ul style="list-style-type: none"> ■ Pass-through: (1) RS232C (2) USB Hub ■ Bluetooth wireless connection 																			
Power Supply	DC 7V~36V to prevent misuse																			
Power Consumption	3~5W																			
MTBF	25,000 hrs																			
Certification	CE/FCC class A																			
Rotation Angle	Vertically: 36 degree Horizontal: 270 degree																			
Physical Dimension																				
Head (W x D x H)	215 x 57 x 92 mm																			
Support (H x Ø)	Long: 250 x 34 mm; Short: 117 x 34 mm																			
Base (W x D x H)	200 x 120 x 27 mm																			
Weight	N.W. 0.8 kg																			
Environment																				
Operation Temperature	5~45°C																			
Storage Temperature	-20~70°C																			
Operation Humidity	15%~80% RH																			
Storage Humidity	10%~90% RH																			

Product specification is subject to change without prior notice.

