

Thermal printer 58 mm



EC-PM-5890X

Features

- Command protocol is based on ESC/POS standard
- Low-noise thermal printing
- Various Layouts are possible by using page mode.
- Repeated operation and copy printing are possible.
- Character font size(12*24 font&24*24 font)optional.
- Easy paper-roll installation.
- Easy paper jam clearance.
- Easy maintenance for tasks such as head cleaning.
- Built-in interface provides control capability for cash drawer.



Specifications

Print method	Thermal line printing
Print speed	90mm/ sec
Paper width	58mm
Print columns	384dots/line
Print character	ANK Characte
Font A	12*24 dots
Simplify/Traditional	24*24 dots
Language	English/French/German/Denish/Spanish/Japanese/Korean
Interface	Parallel/Serial/USB/Ethernet
Reliability print	100Km
Power supply	DC 12V
Cash Drawer	DC 12-24V/1A
Temperature	0~45°C
Paper thickness	0.06~0.08mm
Dampness	10~80%
Barcode mode	JAN13(EAN13)/JAN8(EAN8)/ CODE39
Drivers	Win9x/WinME/ Win2000/WinNT/ WinXP,compatible with EPSON,SAMSUNG
Print command	compatible with ESC/POS
External dimension	140*225*135mm(W*D*H)