

PARTNER

CARE . TRUST . RESPONSIBILITY

PT-8850

PT-8950



Biometric



i-Button



Keypad



MSR

High Performance POS Terminal PT-8850/8950 Series Special Feature

- Scalable high performance Processor Options-
 - * Intel Core 2 Duo 2.13GHz
 - * Intel Pentium Dual-core 1,8GHz
 - * Intel Celeron 2.0GHz
- 15" or 17" Dual Backlight Industrial Grade LCD
- Powered USB
- Gigabit Ethernet

Optional

- Solid State Drive
- Dual display (with or without touch)
- Support 2nd HDD
- Fingerprint reader
- KB-32 keypad
- Magnetic card reader
- RFID reader
- Rear VFD Customer display
- iButton

PT-8850/8950 Series

The PT-8850 series is a top-of-the-line POS terminal system with an impressive technological configuration. The PT-8850 series has variety choice of high performance CPU-Intel Core™ Duo, Intel Pentium Dual-core or Intel Celeron. Whichever configuration you choose, outstanding processing power is guaranteed.

The PT-8850 series is also available with an additional attached customer facing 15" touch LCD display offering unlimited digital signage solutions. This means customers can follow the checkout transaction while providing visual content to help drive up-selling or education of upcoming sales and events. The PT-8850 series has limitless configurations when considering customer marketing ideas. The space saving design and easy set up make the PT-8850 the system of choice for the discerning environment.

| Item | PT-8850 | PT-8950 |
|---|--|--|
| CPU Type | Intel Core™ 2 Duo E6400 2.13GHz or Intel Pentium Dual-core E2160 1.80GHz or Intel Celeron 440 2.0GHz | |
| Memory | 1GB (up to 4 GB) | |
| LCD | 15" Active TFT color LCD, resolution 1024 x 768 | 17" Active TFT color LCD, resolution 1280 x 1024 |
| Touch | 5-wire Resistive touch (RS-232 interface) | |
| Storage | 3.5" type SATA HDD (support 2 HDD) | |
| Ethernet | 10/100M/1000 Mbps | |
| I/O Interface | 6 * COM ports (COM1~4 at back I/O provides DC +5V/12V with BIOS setting, COM5~6 on M/B) 1 * DB-15 VGA port 1 * DB-25 for LPT port 1 * RJ11 port for 2 cash drawer(+24V) 1 * PS2 Keyboard port 1 * PS2 Mouse port 1 * RJ-45 LAN port with activity and link LEDs 2 * Audio ports (1 * Line-out , 1 * MIC-in) 4 * USB 2.0 ports (2*powered USB DC+12V and DC+24V on rear, 2 on front) | |
| Optional Peripherals | 3 tracks magnetic reader Customer display module (2 x 20 VFD) 802.11 b/g/n Mini PCI-e Module support WLAN function Biometric Reader or Smart Card Reader or I-Button or RFID reader KB-32 32-keys keypad 2 nd monitor(Dual screen) SSD (8850/8950) | |
| Expansion Options | 1 * Mini PCI-e | |
| Operation System | Windows Vista, XP, XP embedded, Linux (Fedora) , WEPOS, POSReady | |
| Dimensions | 344mm (W) x287mm (D) x 375mm (H) | |
| Power Supply | AC100~240V 220watt | |
| Operating Temperature | 0°C ~ +40°C | |
| Storage Temperature | -20°C ~ +60°C | |
| Operating & Storage Humidity | 10%~80% | |
| Certification | CE, FCC Class A, UL, cUL, CB, VCCI, BSMI, CCC | |

* specification subject to change without prior notice



0-60 degrees tilt angle



15" Dual Display



Rear Customer Display



17" Touch Screen



Support Multi Reader



Spill proof design



CARE . TRUST . RESPONSIBILITY

Partner Tech Corporation

| | | | |
|---------------|-------------------------|---------------------------|-----------------------------------|
| Taiwan | TEL:+886-2-29188500 | FAX:+886-2-29153405 | E-mail:sales@partner.com.tw |
| USA | TEL:+1-949-598-1888 | FAX:+1-949-598-0088 | E-mail:sales@partnertechcorp.com |
| Europe | TEL:+49 (0)40 450 635-0 | FAX:+49 (0)40 450 635-130 | E-mail:info@partner-tech.eu |
| UK | TEL:+44 (0)1928 579 707 | FAX:+44 (0)1928 571 308 | E-mail:sales@partnertech-uk.com |
| China | TEL:+86-21-67696667 | FAX:+86-21-67696699 | E-mail:sales@partnertech.com.cn |
| Korea | TEL:+82-2-2090-7559 | FAX:+82-2-2090-7558 | E-mail:adams_c@partnertech.com.cn |

