

9-pin, serial dot

TM-U375



High-Performance 1.5 Station Printer

Print method	9-pin, serial impact dot matrix
Print font	Font 5 x 9 / 7 x 9 Column capacity (columns) ... 33 / 40 Character size (mm) 1.6 (W) x 3.1 (H) / 1.2 (W) x 3.1 (H) Character set 95 Alphanumeric, 32 International, 128 x 9 Graphic Characters per inch 13.3 cpi / 16 cpi
Interfaces	RS-232, Bi-directional parallel
Data buffer	4 KB or 40 bytes
Print speed	3.5 lps (at 40 columns, 16 cpi), 5.4 lps (at 20 columns, 16 cpi)
Paper	Dimensions (mm) Roll paper: 76.0 ± 0.5 (W) x dia. 83.0 Slip: 70 (W) x 160 (L) to 182 (W) x 257 (L) Validation: 135 (W) x 70 (L) to 182 (W) x 257 (L) Thickness (mm)..... Roll paper 0.06 to 0.085 / sheet Slip: 0.09 to 0.12 (Total thickness 0.09 to 0.31)
Copy capability	Roll Paper: One original and one copy Slip: One original and two copies
Inked ribbon	ERC-38 (Purple, Black)
Ribbon life	Purple: 4 x 10 ⁶ characters, Black: 3 x 10 ⁶ characters
Power	24 VDC ± 10%
Power consumption	Approx. 1.4 A
D.K.D.function	2 drivers
Reliability	MTBF: 18 x 10 ⁴ hours MCBF: 18 x 10 ⁶ lines
Overall dimensions (mm)	186 (W) x 327 (D) x 145 (H)
Mass (Approx.)	4 kg
EMI standards	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Power supply	PS-170 (option)
Safety standards	UL / CSA / TÜV (EN60950)

Standard 1.5 Station Printer

Basic 1.5 station model with exceptionally low height. Features a movable platen and easy-to-use design for simple roll paper loading, slip insertion and maintenance.

